

## Security Mesh - HD1

### Description

Heavy Duty Security lath suitable for internal wall security, partitions, ceilings and roofs.

Mesh aperture - 42.93 LW x 14.22mm SW

Strand thickness - 2.69mm, 8.59kg.m<sup>2</sup>

Can be installed at the time of construction into internal or external walls (solid or stud), ceilings and roofs, or can be retro-fitted whilst refurbishment is carried out. The option of finishing with dry lining or render is not lost, as our range covers both options.



### Typical Applications

- Cash handling Stores
- Control rooms
- Firearm Stores
- Computer Rooms
- Remote Facility Security
- Wholesale and Retail outlets
- Petrol Station Kiosks
- High Volume Goods Store
- Secure Units
- Pharmaceutical Stores

<b>Application</b>	Heavyweight option for Security in walls, partitions and ceilings
<b>Material Finish</b>	Mild Steel, Galvanised, Painted
<b>Production Process</b>	3mm thick flattened mesh
<b>Weight kg/m<sup>2</sup></b>	8.59
<b>Stock Sheet Sizes (mm)</b>	2440 x 1220 LW SW

### Installation

Easily fixed to brickwork, blockwork, stud partitioning, ceiling joists and roofs in metal or timber. It is important to note that the sheets should be butted together, and not overlapped. Suggested fixings for popular applications are shown below. For additional security we suggest reducing the spacing shown when fixed adjacent to door or windows.

