

Data Sheet

Slate Ventilator 600mm x 300mm

Hooded slate ventilator

Application

- For high or low level roof space ventilation
- Slate replacement ventilator
- For new build and/or refurbishment projects
- To reduce risk of condensation
- Suitable for soil ventilation and mechanical extraction
- Direct replacement for 600mm x 300mm slate
- Trim for replacement for 500mm x 250mm slate

Product Features & Benefits

- To allow 10,000mm² free vent area
- Suitable for both 600mm x 300mm & 500mm x 250mm slates
- Optional adaptor kit available to 110mm diameter pipe
- Meets requirements of BS5250:2021 Management of moisture in buildings
- Provides compliance with BS5534
- Complies with Building regulation approved documents F1 & C2
- Assists in meeting requirements of the domestic ventilation compliance guide 2010
- Prevents ingress of water, birds, vermin and large insects
- Lightweight and resistant to corrosion and rotting
- Acid rain resistant and UV stabilised

Materials

- Manufactured in Black Polypropylene.

Installation Guide

See separate detailed fixing installation

Product Range

Description	Ventilation	Length	Width	Diameter	Pack Qty
600 x 300 Universal hooded slate ventilator SRV10U	10,000mm ²	600mm	300mm	-	10's
Soil pipe adaptor kit SPA – hooded slate	9500mm ²	440mm	-	110mm	10's



- **600 x 300 Universal hooded slate ventilator SRV10U**
Minimum roof pitch of 22.5°
Maximum roof pitch of 55°



- **Soil pipe adaptor kit SPA – hooded slate**
Connects slate vent to standard 110mm pipework

