

## Data Sheet

### Universal Slate Ventilator 600mm x 300mm

Discreet Low profile solution for roof space & soil/mechanical terminal ventilation terminal ventilation

#### Application

- To ventilate direct to roof space
- High or low level roof space ventilation
- Mechanical extract/inlets terminal with the additional soil pipe adaptor kit
- Design accommodates 600mm x 300mm, 500mm x 250mm and 450mm x 230mm slate sizes
- Minimum roof pitch of 22°
- Maximum roof pitch of 55°

#### Product Features & Benefits

- To allow 10,000mm<sup>2</sup> free vent area
- Discreet low-profile design
- Optional adaptor kit available to 110mm diameter pipe
- Meets requirements of BS5250:2021 Management of moisture in buildings
- Provides compliance with BS5534
- Complies with Building regulation approved documents F1 & C2
- Assists in meeting requirements of the domestic ventilation compliance guide 2010
- Prevents ingress of water, birds, vermin and large insects
- Lightweight and resistant to corrosion and rotting

#### Materials

- Slate vent manufactured in Black Polypropylene.
- Adaptor manufactured in Polypropylene.
- Flexible tube manufactured in Polyethylene.

#### Installation Guide

Batten cutting required, see separate detailed fixing installation

#### Product Range

Description	Ventilation	Length	Width	Diameter	Pack Qty
Universal In Line slate ventilator ILSRV10U	10,000mm <sup>2</sup>	455mm	400mm	-	5's
Soil pipe adaptor kit ILSPAU – universal in line slate	800mm <sup>2</sup>	510mm	-	110mm	5's



- **Universal In Line slate ventilator ILSRV10U**  
Minimum roof pitch of 22°/25° depending on head lap  
Maximum roof pitch of 55°  
Batten cutting required



- **Soil pipe adaptor kit ILSPAU – universal in line slate**  
Used to connect standard 110mm pipework to tile ventilators,  
510mm long

